

SERIES 26 - MAX. 26 MM CUTTING DIAMETER

Main characteristics STILO-S26

CUTTING DIAMETER	max. Ø 26 mm	SUGGESTED APPLICATION	Steel, ACSR, copper and aluminium
------------------	--------------	-----------------------	-----------------------------------

4



SE26ST



Set STILO-S26

STILO-S26 - Battery operated cutting tool

The STILO26 battery powered hydraulic cable cutter is suitable for cutting through hard steel up to a thickness of 26mm

Technical characteristics:

- Right or left hand ergonomic non-slip cushioned grip
- Open cutting head design
- 360° tool head rotation
- Lightweight and compact design
- Extremely fast work due to triple axial piston pump
- DataTrack mini USB-port for connectivity
- Cutting curve and error message output
- No aborted cutting cycles due to ongoing monitoring of the remaining battery running time
- Multifunction LED indicator lights even to indicate the maintenance intervals
- LED battery charge indicator
- Heavy duty blades
- Soft start and quick stop increase the service life
- Manual return possible in any position
- Shutdown and automatic return after completion of a cutting cycle
- Automatic energy-saving mode after approx. 5 minutes

Tool dimensions: 457 x 126 x 82 mm
 Tool weight (with battery): 4,2 kg

Description	Order No.	Dimensions	Weight
Set cutting tool STILO26	STILO-S26	450 x 500 x 140 mm	6,9 kg
Cutting insert Steel	SE26ST	-	40 g

Accessories see page 209-212

Set equipment:

- Test report
- Battery-operated hydraulic cutting tool
- Battery 18 V/1,5 Ah Li-Ion (RA12)
- Battery charger (LG8)
- USB-cable
- Software (CD)
- Rigid plastic case

CUTTING RANGE TABLE STILO-S26

Sector of use:	Tensile strength N/mm ²	<Ø 9 mm	Ø 10 mm	Ø 11 mm	Ø 12 mm	Ø 13 mm	Ø 14 mm	Ø 15 mm	Ø 16 mm	Ø 17 mm	Ø 18 mm	Ø 19 mm	Ø 20 mm	Ø 21 mm	Ø 22 mm	Ø 23 mm	Ø 24 mm	Ø 25 mm	Ø 26 mm
		Copper	Rope and cable	<410															
	Bar	<250																	
	Bar	<300																	
Aluminium	Rope and cable	<200																	
	Bar	<160																	
	Bar	<340																	
Aldrey	Cable	<340																	
Alu/Steel	Rope	<1800																	
	Rope (>200 wires)	<180																	
Steel	Bar	<420																	
	Bar	<600																	
	Rope	<2200																	